

# KAYAYA SAFETY

KAYASAFETY.COM

## DATA SHEET

LUPA STATİK 12 MM  
LUPA STATIC 12 MM



## LUPA STATİK 12 MM

STATIC ROPE  
STATİK HALAT

(EN)

- Designed for rescue operations and rope Access techniques.
- Made of High Tenacity Polyamide Fiber (S/Z Twist).
- Formed by core and protector cover.
- Excellent hand-grip feature.
- High resistance against abrasion.
- High UV resistance.
- Identification tape inserted (with information of relative standard, type of rope, brand).

(TR)

- Statik 12 mm, kurtarma operasyonları, iple erişim teknikleri ve zorlu çalışma ortamları için tasarlanmıştır.
- Yüksek mukavemetli polyamid liflerin S/Z bükümünden üretilmiştir.
- Bir iç kısım ve iç kısmı koruyan dış mantodan oluşmuştur.
- Mükemmel elle tutuş özelliği sağlar.
- Sürtünmeye karşı yüksek dayanım sağlar.
- Güneş ışınlarından korunması için yüksek UV dayanımına sahiptir.
- İp içerisinde sahip olduğu standart, ip tipi ve marka bilgilerinin bulunduğu ip boyunca devam eden bilgi şeridine sahiptir.

Dia/Çap (mm)	12
Type/Tip	A
Weight/Ağırlık (gr/m)	92
Breaking Load/Kopma Mukavemeti (kN)	40,5 kN
Breaking Strength with Knot/Düğüm ile Kopma Direnci	22 kN
Sheat Slippage/Kılf Kayması (%)	0,5
Static Stretching/Statik Esneme (%)	% 2,5
Düğüm Esnekliği/Knot Flexibility	1,16
Stitched Eyes Strength/Dikişli Göz Mukavemeti	25 kN
Eight Knot Strength/Sekiz Düğümü ile Mukavemeti	22 kN
Standard/Standart	EN 1891

Standard Lengths/Standart Uzunlukları;

- 50, 100, 150 & 200 m
- 50, 100, 150 & 200 m
- 50, 100, 150 & 200 m