



DATA SHEET

HWPB SERIES RETRACTABLE FALL ARRESTER GERİ SARIMLI DÜŞÜŞ DURDURUCU



HWPB-3,5



HWPB-5,5



HWPB-7



HWPB-9



Housing Material/Gövde Malzemesi: HDPE

Line Material/Halat Malzemesi: Dyneema® Webbing/ Dyneema® Kolon

Standard/Standart: FprEN360:2022

HWPB-SERIES RETRACTABLE FALL ARRESTER GERİ SARIMLI DÜŞÜŞ DURDURUCU

(EN)

- Lightweight and durable ABS housing equipped with a swivel attachment point.
- Retractable lifeline made of Dyneema® webbing.
- Operating temperature range: -40 °C to +50 °C.
- Shock absorber system which damps the impact force to 4 kN in the body
- Horizontal operation with sharp edge resistance

(TR)

- Döner bağlantı noktasına sahip, hafif ve sağlam ABS plastik gövde.
- Dyneema® kolondan üretilmiş geri sarılabilen bağlantı hattı.
- Çalışma sıcaklık aralığı: -40°C ile +50°C
- Gövde içerisinde darbe kuvvetini 4 kN'a sönmleyen şok emici sistem
- Keskin kenar dayanımı sayesinde yatay çalışabilme

	Gate Opening Ağız Açıklığı	Length Uzunluk	Working Load Çalışma Yüğü	Weight Ağırlık	Dimensions Boyutlar
HWPB-3,5	25 mm	3,5 m	136 kg	1,50 kg	275x110x78 mm
HWPB-5,5	25 mm	5,5 m	136 kg	1,70 kg	300x120x85 mm
HWPB-7	25 mm	7 m	136 kg	2,0 kg	300x141x84 mm
HWPB-9	25 mm	9 m	136 kg	2,8 kg	335x168x93 mm

