

## TUMBLER MOBİL ANKRAJ DİKMESİ MOBILE ANCHOR POST

## KULLANIM KILAVUZU USER GUIDE



### A Ürün Kullanım Raporu Product Usage Report

- A.1- Ürün Seri No**  
Serial Number : .....
- A.2- Üretim Tarihi**  
Date of Production : .....
- A.3- Sevk Tarih**  
Date of Delivery : .....
- A.4- Kaşe İmza**  
Stamp & Signature : .....
- .....
- .....
- .....
- .....
- A.5- Ürün İtk Kul. Tar.**  
Date of first use : .....
- A.6- Kullanıcı Ad/Soyad**  
Name&Surname of user : .....

KYS\_TUMBLER\_KLK\_01\_22072020\_A

### B Ürün Yıllık Kontrolleri Annual Product Inspections

B.1 No Nu	B.2 Yıllık Kontrol Tarihi Inspection Date	B.3 Gelecek Yıl Kontrol Tarihi Next Inspection Date	B.4 Kontrol Eden Ad/Soyad Inspected by
1			
2			
3			
4			
5			
6			
7			

### C TUMBLER (TR) Mobil Ankraj Dikmesi (EN) Mobile Anchor Post EN 795:2012 Type A CEN/TS 16415 A:2013




**Test Eden Onaylı / Testing Laboratory**  
APAVE SUDEUROPE SAS13322 MARSEILLE CEDEX 16 – France  
**Tel.** +33 (0) 4 76 53 52 22 **Fax** +33 (0) 4 76 53 32 40

### D (TR) Ürün Bileşenleri (EN) Product Components



### E (TR) Ürün Etiketi (EN) Product Label



**F****(TR) Ürün Ölçüleri****(EN) Product Measurements**

Açık Boy / ClosedLength : 1060 mm  
Kapalı Boy / OpenedLength : 1400 mm

**TR****A- Ürün Kullanım Raporu**

- A-1-** Ürün Seri No
- A-2-** Üretim Tarihi
- A-3-** Sevkiyat Tarihi
- A-4-** Kaşe İmza
- A-5-** Ürün İlk Kullanım Tarihi
- A-6-** Kullanıcı Ad/Soyad

**B- Ürün Yıllık Kontrolleri**

- B-1-** No
- B-2-** Yıllık Kontrol Tarihi
- B-3-** Gelecek Yıl Kontrol Tarihi
- B-4-** Kontrol Eden Ad/Soyad

**C- Mobil Ankraj Dikmesi**

EN 795:2012 Type A CEN/TS 16415 A:2013

**Test Eden Onaylı**

APAVE SUDEUROPE SAS 13322 MARSEILLE CEDEX 16 – Fransa  
Tel. +33 (0) 4 76 53 52 22 Fax +33 (0) 4 76 53 32 40

**D- Ürün Bileşenleri**

- D-1-** Üçlü Ankraj Noktası
- D-2-** Orta Kademe
- D-3-** Ana Gövde
- D-4-** Zemin Montaj Plakası
- D-5-** Dengeleme Ayağı

**E- Ürün Etiketleri**

- E-1-** Marka
- E-2-** Ürün Adı
- E-3-** Malzeme
- E-4-** Kullanma Kılavuzunu Oku
- E-5-** Standart
- E-6-** Üretim Yılı
- E-7-** Seri Numarası
- E-8-** Kullanıcı Sayısı

**(TR) Kullanım Alanları****(EN) Area of Use**

Şekil - 1 / Figure - 1

**1- Kullanım Alanı**

- \* Bu kullanım kılavuzu ekipmanınızı nasıl doğru kullanacağınıza açıklar. Sadece burada belirtilen teknikleri kullanınız ve uygulayınız.
- \* Buradaki uyarıcı semboller sizi sadece bazı risklere karşı uyarılmaktadır, ancak bütün riskleri belirtmez.
- \* Detaylı bilgi için [www.kayasafety.com](http://www.kayasafety.com) web sitemizi ziyaret ediniz.
- \* Bu ürün ankraj noktası oluşturmak için tasarlanmıştır.
- \* Tumbler Mobil Ankraj Dikmesi EN 795:2012 Type A, CEN/TS 16415 A:2013 normlarına uygun olarak sertifikalandırılmıştır.

**2- Sorumluluk**

- \* Bu ürünü kullanmadan önce kullanım kılavuzunu okuyunuz ve anladığınızdan emin olunuz. Kullanım amacına yönelik özel eğitim alınmalıdır.
- \* Yüksekte çalışma; ciddi yaralanmalara ve ölümlere yol açabilecek tehlikeli aktivitelerdir. Uygun kullanım tekniklerini ve güvenlik yöntemlerini öğrenmek ve pratikte uygulamak kullanıcının sorumluluğudur. Tumbler Mobil Ankraj yalnızca bu konuda eğitim almış uzman personel tarafından veya bu personelin gözetiminde kullanılmalıdır. Yanlış kullanım ya da uygun olmayacak şekilde kullanılması halinde ciddi yaralanmalara ve ölümcül kazalara neden olabilir.
- \* Tumbler Mobil Ankraj tasarım amacı dışında kullanılmamalıdır.
- \* Bu donanım tek başına yüksekte çalışmak için uygun değildir, bu donanımla beraber CE sertifikalı Tam Korunmalı Düşüş Durdurma Kemer (EN 361, EN 358), Şok Emicili Lanyard (EN 355, EN 354), kancalar (EN 362), v.b. ekipmanlar ile beraber kullanılmalıdır.
- \* Bu ürün minimum -30°C ve maksimum +70°C sıcaklıkları arasında kullanılmalıdır.

**3- Ham madde;**

- \* Zemin plakası S235JR Çelik,
- \* Ana Gövde Alüminyum,
- \* Ankraj Plakaları 316 Kalite Paslanmaz Çeliktir.

**4- Ankraj Noktası (EN 795/A:2012, CEN/TS 16415 A:2013)**

- \* Aynı anda maksimum 3 kullanıcının kullanımı için uygundur. Bu cihazın minimum kuvvet dayanımı 14kN'dir

**4.1- Ürün Montajı**

- \* Tumbler Mobil Ankraj Yüksekte Çalışma Eğitim sertifikalı ve KAYA SAFETY tarafından kurulum eğitimi alarak yetkilendirilmiş kişiler tarafından yapılmalıdır. Sistemin bütününe sorumluluğu kurulumu gerçekleştiren firmaya veya kişiye aittir.

**4.1.1 - Zemin Plakasının Montajı ;**

- \* M12 çelik dübelleri veya M12 civataları zemin plakasının delikleri ile eşleşecek şekilde zemine montajlanacaktır ve ardından zemin plakası yere sabitlenecektir.

**4.1.2 - Tumblerin Zemin Plakasına Montajı**

- \* Tumbler bağlantı ayakları zemin plakası üzerine geçirilerek Metrik 16 civata ve somun ile montaj tamamlanır.

#### 4.1.3 - Tumbler Seviye Ayarı;

\* Tumbler üzerindeki sıkıştırma topuzu ve civata sökülür. Boyu yükseltildikten sonra eşleştirilen deliklerden tekrar civata geçirilerek sıkıştırma topuzu sıkılır ve montaj tamamlanır.

#### 4.1.4 - Ankraj Noktalarına Bağlantı

\* Tumbler üzerinde 3 adet ve zemin plakasında 1 adet olmak üzere 4 adet ankraj noktası bulunmaktadır. Kişi bu noktalardan Tam korumalı düşüş durdurma kemeri bulunan «A ile işaretli bağlantı noktalarından (EN 361, şok emicili kemeri bulunan «A ile işaretli bağlantı noktalarından (EN 361)

#### 4.2. Ürün Kullanımı

\* Tumbler Mobil Ankraj Dikmesinin Figür 1'de belirtilmiş 4 ankraj noktası bulunmaktadır. Aynı anda 3 kişi kullanılabilmektedir.

### 5. EN 365 Standardına ilişkin genel bilgilendirme

#### 5.1 Kurtarma Planı

Ürün kullanımını sırasında herhangi bir zorluk ile karşılaşılması durumunda çok hızlı bir şekilde kurtulması için bir kurtarma planının hazırlanmış olması zorunludur.

#### 5.2 Ankraj noktası

Kullanım esnasında ankraj noktaları kullanıcının üstünde veya en azından göğüs hizasının üzerinde olmalıdır. Bu hizanın altında kullanım ciddi yaralanmalara veya ölüme yol açabilir. Kullanım şekli ve yönüne göre yapıya aktarılacak maksimum yük 19,6kNm'dir.

#### 5.3 Çeşitli Durumlar

\* Tumbler Mobil Ankraj bir düşüş durdurma sisteminde sadece ankraj olarak kullanılmalıdır.

\* Bir düşüş durdurma sisteminde, her kullanımdan önce bir düşüş durumda kullanıcının zemine veya başka bir yüzeye çarpmasını engellemek için kullanıcının altında kalan mesafenin ölçülmesi gerekir.

\* Birçok ürün beraber kullanıldığı zaman tehlikeli bir durum ortaya çıkabilir. Bunun için bir ekipmanın güvenlik fonksiyonunun diğer ekipmanın güvenlik fonksiyonunu tehlikeye atmamalıdır.

\* Kullanıcı tıbbi olarak yüksekte çalışmaya uygun olmalıdırlar. Yüksekte çalışmanın ölümcül kazalara neden olabileceğine dair uyarılmalıdırlar.

### 6 Ürün Kontrolü ve Doğrulama

**6.1 Her kullanımdan Önce:** Yüksekte çalışma ürünleri kişiye özel olarak kullanılmalıdır. Bu ürünler her kullanımdan önce ve sonra düzenli bir şekilde kontrol edilmeli ve tespit edilen bilgiler ürün kontrol defterine kayıt edilmelidir.

Ürünü aşağıdaki kontrol kriterlerine göre kontrol ediniz.

\* Montajın yapıldığı zemin üzerinde bir deformasyon olup olmadığı

\* Tumbler Mobil Ankrajın üzerinde her hangi bir yıpranma, çatlak, kırılma vb olup olmadığı,

\* Sistem bileşenler üzerine herhangi bir kimyasal etki edip etmediği,

#### 6.2 Her kullanım sırasında:

Kullanım sırasında ürün bir sistem ile beraber kullanıldığında, tüm sistemin birbiri ile uyumlu olmalıdır. Sistem içindeki tüm ekipmanların bir diğer ekipmana göre doğru konumlandığından emin olunuz.

### 7.Kaya Genel Bilgilendirme

#### 7.1 Ürün Ömrü:

\* Metal malzemelerin teorik kullanım ömrü bulunmamaktadır. Ürün yılda en az 1 kere periyodik kontrolleri yaptırılarak ürünün kullanımına uygun olup olmadığı belgelenmelidir. Yıllık periyodik kontrolü yapılmamış ürünün kullanımından KAYA SAFETY sorumlu değildir.

\* Tumbler Mobil Ankraj alüminyum, paslanmaz çelik ve kestamit malzemenin üretilmiştir. Bu malzeme atmosferik korozyona karşı oldukça dirençlidir. Ürünün kullanım yerine bağlı olarak değişen zamanlarda (Endüstriyel sahalar; demir tozları ve kimyasallar, denize yakın sahalar; havada asılı bulunan tuzlar gibi daha kısa sürelerde, Kırsal alanlarda; daha uzun sürelerde ) ürün üzerinde yüzeysel pas lekeleri görülebilir.

Bu yüzeysel lekeler uygun bir bakım programı ile giderilebilir.

\* Ürünün kullanıma devamı yönünde verilecek karar ancak; yıllık periyodik kontrollerinin üretici veya onun yetkilendirdiği kişiler tarafından yapılması ve muayene sonrasında uygunluk verilmesi neticesinde verilebilir.

Aşağıdaki durumlarda ürün üreticiye geri gönderilmeli veya imha edilmelidir;

\* Ürün üzerinde paslanma belirtileri gözlemlenmiş ise,

\*Ürün bir kontrol sırasında kullanıma uygun bulunmadı ise ve sizin bundan bir şüphemiz var ise,

\* Ürün standardında, yasalarda, kullanım tekniğine uyumu ile ilgili bir değişiklik ve benzeri durumlarda.

\* Ürün bir düşüş yaşamış ve yüke maruz kalmışsa yetkin bir kişinin yazılı onayı olmadan kullanılmamalıdır

#### 7.2 Ürün Depolanması:

Ürün kendi özel ambalajında ve kullanım kılavuzu ile birlikte, üzerinde modeli, standardı yazılı olarak satışa sunulmuştur. Ürünü kendi çantası içinde muhafaza ediniz.

Ürünün depolama alanlarında aşağıdaki kriterler göz önünde bulundurulmalıdır;

\* Ürünün depolanması sırasında metale zarar verecek kimyasallar ile temasından kaçınılmalıdır.

\* Depolama alanında ( asitler, solventler v.b. ) ürüne zarar verecek maddelerden uzak tutulmalıdır.

\* Ürün ısı kaynaklarından uzak tutulmalıdır.

\* Ürünü aşındırıcı ve asit türevi kimyasallardan uzak tutunuz.

#### 7.3 Ürün Bakımı:

\* Ürüne her kullanımdan sonra bakım yapmak ürünün kullanım ömrünü uzatır. Ürünü metal temizleme ürünleri ile temizleyiniz. Daha fazla bilgi için info@kayasafety.com adresinden bize ulaşabilirsiniz.

#### 7.4 Değişim ve Tamir

\* KAYA SAFETY'den önceden yazılı izin alınmadan ürün üzerinde herhangi bir değiştirme, tamir veya ekleme yapılmamalıdır. Ürün üzerinde herhangi bir tamir sadece üretici ( KAYA SAFETY ) tarafından veya KAYA SAFETY nin yetkilendirdiği yetkili kişiler tarafından yapılabilir. Yapılan tüm tamir ve bakım çalışmaları sadece üretici (KAYA SAFETY) nin vereceği talimatlar doğrultusunda yapılmalıdır. Aksi takdirde oluşacak tehlikelerden KAYA SAFETY sorumlu değildir.

\* Ürünün kullanım, bakım ve tamirine ilişkin talimatlar istenildiği takdirde o ülkede ki yetkili distribütör firmadan ülkenin kendi dilinde temin edilebilir. Lütfen ülkenizde ki distribütör firma ile iletişime geçiniz.

#### 7.5 Ürünün Taşınması:

Ürün taşıma sırasında, nem ve kimyasallardan uzakta, keskin kenarlardan, başka diğer cisimler ile temas etmeyecek şekilde taşınmalıdır.

#### 7.6 Ürün Periyodik Kontrolü:

Ürününüzü her kullanımdan önce veya belirli periyotlarda mutlaka yılda en az 1 defa üreticiden veya üreticinin yetkilendirdiği yetkin bir personel tarafından kontrol ettirip kullanım için tavsiye alınmalıdır.

Ürün kontrolünden sonra aşağıdaki bilgilerin mutlaka kayıt altına alınması tavsiye ederiz.

\* Ürün Tipi, Model, Üretici iletişim bilgileri, Serin Numarası, Üretim Tarihi, Satınalma tarihi, İlk kullanım tarihi, Bir sonraki periyodik kontrol tarihi, problemler, yorumlar, kontrolü yapan uzmanın isim ve soy ismi. Daha fazla bilgi için www.kayasafety.com

#### 7.7 Garanti:

Bu ürün her türlü malzeme ve üretim hatlarına karşı 10 yıl garantilidir. Garanti süresi şu durumlarda geçerli değildir: Yanlış kullanım alanları, kesilme, yırtılmalar, oksitlenme, ürünün tamir edilmesi veya üzerinde değişim yapılması, kazalarda oluşan ürün yıpranmaları.

**Uyarı:** Kullanmadan önce mutlaka kullanım talimatlarını dikkatle okuyunuz.

**Üretici:** KAYA YAPI İÇ MİM. TAS. İNŞ. DEN. TAAH. SAN. ve TİC. A.Ş.

**Adres:** GOSB. 1000 Sok. No:1015 Çayırova 41480 KOCAELİ / TÜRKİYE

**T:** + 90 262 677 19 00

**F:** + 90 262 677 19 01

**e-mail:** info@kayasafety.comweb: www.kayasafety.com

## A- Product Usage Report

- A-1- Serial Number
- A-2- Date of Production
- A-3- Date of Delivery
- A-4- Stamp & Signature
- A-5- Date of First Use
- A-6- Name & Surname of user

## B- Annual Product Inspections

- B-1- Number
- B-2- Inspection Date
- B-3- Next Inspection Date
- B-4- Inspected by

## C- Mobile Anchor Post

EN 795:2012 Type A CEN/TS 16415 A:2013

### Testing Laboratory

APAVE SUDEUROPE SAS13322 MARSEILLE CEDEX 16 – France  
Tel. +33 (0) 4 76 53 52 22 Fax +33 (0) 4 76 53 32 40

## D- Mobile Anchor Product Components

- D-1- Triple Anchor Points
- D-2- Middle Section
- D-3- Main Body
- D-4- Ground Mounting Plate
- D-5- Balancing Leg

## E- Product Label

- E-1- Trade Mark
- E-2- Product Name
- E-3- Material
- E-4- Read User Guide
- E-5- Standard
- E-6- Production Year
- E-7- Serial Number
- E-8- Max. Number of Users

## 1- Area of Use

- \* This manual guides for the proper use of equipment. Only the mentioned techniques must be used and applied.
- \* Symbols in this manual warn about certain risks, but do not include all. Please visit [www.kayasafety.com](http://www.kayasafety.com) for further information.
- \* Tumbler Mobile Anchor is designed to create an anchor point on lattice masts, posts or concrete.
- \* Tumbler Mobile Anchor is certified in accordance with EN 795/A:2012, CEN/TS 16415 A:2013 norms.

## 2- Responsibility

- \* Make sure that you have read and understand the user guide. Proper training has to be taken for correct use.
- \* The users must read and fully understand these instructions or have the instructions explained in detail before using this equipment. Failure to observe these instructions could result in serious injury or death.
- \* Working at height is acknowledged as one of the most dangerous activities that cause fatal accidents. Prior to use, all workers must be trained in the proper use of the systems. A training and instruction review should be repeated at regular intervals.
- \* Tumbler Mobile Anchor must not be used for anything other than its intended purpose
- \* Tumbler Mobile Anchor is not suitable to use this system as material handling system.
- \* When the anchor device is used as part of a fall arrest system, the user has to be equipped with a means of limiting the maximum dynamic forces

exerted on the user during the arrest of a fall to a maximum of 6 kN.

\* Tumbler Mobile Anchor is aimed to prevent user from falling. However, the system itself is not suitable for working at height, it must also be used together with CE certificated Safety Harness (EN 361, EN 358) energy absorber lanyard (EN 355), hooks (EN 362) and fall arresters (EN 360)

\* Tumbler Mobile Anchor must be connected to a fall arrest attachment, which is marked with "A", on the back or chest of a full body harness (EN 361) using an energy absorber lanyard (EN 355), mobile fall arrester (EN 353-2) or fall arrester (EN 360).

## 3- Raw Material This product's;

- \* Base Plate is made of S235JR Steel,
- \* Main Body is made of Aluminium,
- \* Anchor Plates are made of 316 Grade Stainless Steel

## 4- Anchor Point (EN 795/A:2012, CEN/TS 16415 A:2013)

This anchor device is suitable for use of maximum 3 users at a time. The minimum strength of this anchor device is 14kN.

### 4.1- Installation

\* Installation of this device must be performed by KAYA SAFETY team or an authorized personnel have working at height certificate. The responsibility of installation belongs to the installer company or person.

#### 4.1.1 - Installing Ground Plate;

\* Install M12 steel anchor bolts aligning with holes on the plate and fix the plate to the ground.

#### 4.1.2 - Mounting Tumbler with Ground Plate

\* Insert Tumbler mounting legs on ground plate and complete the assembly with M16 bolt and nut.

#### 4.1.3 - Tumbler Height Adjustment;

\* Unscrew the knob and bolt placed on Tumbler device. Adjust to desired height and align the holes on the body. Insert the bolt through the matching holes and screw the knob back.

#### 4.1.4 - Attaching to Anchor Points

\* There are 3 anchor points on Tumbler body and 1 anchor point on ground plate. User must connect to these points only with certified fall protection equipment.

## 4.2. Product Usage

\* Device has 4 anchor points are shown in **Figure 1**. Maximum 3 user must be attached to device at a time.

## 5. Supplementary information regarding standard EN 365;

### 5.1 Rescue Plan

While using the product, you must have a rescue plan to be recovered from an emergency or difficult situation immediately. Adequately trained personnel and rescue equipment must be on hand for rescue.

### 5.2 Anchor Point

The anchor point of the system comprises this product should preferably be located above the user or should at least be located at the waist level of the user. An attachment point below this level will cause a serious injury or death. The anchor point must conform to the requirements of the EN 795 and CEN/TS 16415 standard and the minimum strength of it must be 14 kN. 19.6kNm maximum loads will be transmitted in service from the anchor device to the structure according to directions of loading relevant to the type of fixing and structure.

### 5.3 Various Situations

- \* A fall arrest harness is the only device allowable for supporting the body in a fall arrest system.
- \* In a fall-arrest system, it is essential to check the required clearance under the user before each use, to avoid any impact with the ground or an obstacle in case of a fall.
- \* Make sure that the anchor point is correctly positioned, in order to limit the risk and the height of a fall.
- \* When using multiple pieces of equipment together, a dangerous situation can result if the safety function of one piece of equipment is affected by the safety function of another piece of equipment.
- \* Users must be medically fit for activities at height.

### **Warning:**

Inert suspension in a harness can result in serious injury or death.

- \* Users must be medically fit for activities at height not to affect the safety of the equipment user in normal and emergency use.
- \* The instructions for use for each item of equipment used in conjunction with this product must be respected.
- \* The instructions for use must be provided to users of this equipment in the language of the country in which the product is to be used.

## **6. Control of product and validation**

### **6.1 Before each use:**

Working at height equipment must be inspected before each use and / or on a regular basis. Findings must be recorded on product control book. Inspection must be performed based on following control criteria.

- \* Where the installation is being made must be checked for a deformation, crack.
- \* Metallic parts must be checked for on any wear or cracks
- \* System components must be checked if they have been in contact with any chemical. If the product has one of the deviations above it should be withdrawn from service immediately. Defects found on the product should not be repaired; manufacturer must be informed about it and user must proceed as per manufacturer's recommendation.

### **6.2 During each use:**

During performing the work at height if the equipment is connected with another system, make sure that all pieces of equipment in the system are correctly positioned with respect to each other.

## **7. Kaya General Information**

### **7.1 Product Life:**

- \* There is no theoretical lifetime of metallic materials. Products must be documented by at least one time per year to determine if the product is safe to use. KAYA SAFETY is not responsible for the use of the product that has no annual periodic control
- \* Tumbler Mobile Anchor is made of stainless steel and aluminum. This material is highly resistant to atmospheric corrosion. Depending on the area of the use superficial rust spots can be seen on the product (In a short time of a period industrial sites; iron powders and chemicals. Areas near sea water; salt in the air like). These superficial stains can be removed with an appropriate maintenance program.
- In all circumstances decision to continue to use the product can only be made if annual periodic control has been performed and resulted positive by manufacturer or a competent person authorized by manufacturer. If the product has one of the deviations below it should be withdrawn from service immediately and should be destroyed to prevent further usage.
- \* It has suffered a heavy shock load or has had a load dropped onto it.
- \* If observed signs of corrosion on the product
- \* If product was recorded not suitable for use during a control and if you have any doubt about a fall.
- \* Changes in standards, legislation and changes related to technical use of it, and similar cases.
- \* It have been used to arrest a fall and not used again until confirmed in writing by a competent person that it is acceptable to do so

### **7.2 Storage:**

Product is comes with its comes. Instruction manual for use and applied standards are written on the product sheet. During the storage keep the product in it's own bag. Storage area of the product should meet following requirements;

- \* Dry, no direct sun light, room temperature
- \* Do not store together with acid, solvents etc.
- \* Keep away from direct heat sources. \* If the product humided during the storage, dry the product in room temperature before usage.
- \* Keep aware from chemicals such as corrosive and acids.

### **7.3 Maintenance:**

Taking good care of the product after each use extends the life of it. Use metal cleaners to clean the product. For detailed information please contact us on [info@kayasafety.com](mailto:info@kayasafety.com)

### **7.4 Changes and repair**

Changing a part, repair and addition to any component of the system is strictly forbidden without written authorization of KAYA SAFETY. Any repairs on products can only be done by manufacturer or qualified persons authorized by the manufacturer. All repair and maintenance work must only be performed in accordance with manufacturer's instructions. KAYA won't be responsible for repairs performed by for unauthorized persons. Manufacturer's instructions for repair and maintenance can be obtained from authorized distributor in the official language of the country in which the item is in service. Please contact authorized distributor in your country.

### **7.5 Transportation of product:**

The product should be transported in a bag to keep it away from moisture, chemicals and sharp edges as well as to protect it getting in contact with another objects

### **7.6 Periodical inspection of product:**

Product must be inspected at least one time in a year by manufacturer or a competent person authorized by manufacturer. Product is going to be marked with a sticker that includes the date of the next or last inspection by Kaya Inspector. During the inspection of product following information should be recorded; Type of the product, model, contact information of producer, serial number, date of production, date of purchase, date of first use, next inspection date, problems, recommendations, name and surname of inspector. For further information visit [www.kayasafety.com](http://www.kayasafety.com)

### **7.7 Guarantee:**

This product has 10 year guarantee against all material or manufacturing defects under proper usage and storage conditions. Guarantee is no more valid if; product is used wrong, tears, cut, corrosion, unauthorised repair of changes on the product, damages caused by accidents.

### **Warning:**

Read user guide carefully before usage. The user manual, periodic examination, information, repair and maintenance instructions should be published in the official language of the country in which, the item is in service.

Please request the user the user manual in your language from your distributor.

**Warning:** Read user guide carefully before usage.

**Manufacturer:** KAYA YAPI İÇ MİM. TAS. İNŞ. TAAH. SAN. ve TİC. A.Ş.

**Address :** GOSB. 1000 Sok. No:1015 Çayırova 41480 KOCAELI / TURKEY

**T :** + 90 262 677 19 00

**F :** + 90 262 677 19 01

**e-mail :** [info@kayasafety.com](mailto:info@kayasafety.com)

**web :** [www.kayasafety.com](http://www.kayasafety.com)

Gebze OSB 1000 Sk. No: 1015 41480

Kocaeli, Turkey

**T :** + 90 262 677 19 00 **F :** + 90 262 677 19 01

**E :** [SATIS@KAYASAFETY.COM](mailto:SATIS@KAYASAFETY.COM)

**KAYASAFETY.COM**